

Spellman High Voltage has been designing, manufacturing and providing CT generators for OEM customers for over three decades. We have unrivaled experience being the first provider of a CT generator used in a commercially available continuous rotating CT scanner in 1985. Since then Spellman has enhanced performance and developed new CT generators year after year, setting the standard for CT generator technology.

Spellman High Voltage has manufactured over 30,000 CT generators. We have the knowledge, capability and experience to provide you with the CT generator technology you need.

Ask about our subsystem capabilities

- **CT Generators from 32kW to 110kW**
- **60-140kV output**
- **Rotational CT up to 240rpm**
- **Fast rise time**
- **Designed to drive industry standard CT tubes**
- **Digital interface allows for ease of integration**
- **OEM customization**



32/42/50kW 16-64 slice single chassis "compact" CT generator



50kW/80kW 16-128 slice "performance" CT generator with grid/Z deflection



110kW 64-264 slice "premier" CT generator for state of the art CT systems

MODEL	32/42/50kW Compact CT Generator	50/80kW CT Generator	110kW CT Generator
Model Designation	CCT70PN32 CCT70PN42 CCT70PN50	CT70PN50 CT70PN80	CT140N110
Input Power	400Vac, 3Ø, +15%/-20%, 50/60Hz		
Auxiliary Input Power	220/230Vac, 1Ø +15%/-10%, 50/60Hz	220/230Vac, 1Ø +15%/-10%, 50/60Hz	Not required
kV Output Range	60kV - 140kV (bipolar, 30kV – 70kV)	60kV - 140kV (bipolar, 30kV – 70kV)	60kV to 140kV Anode grounded
kV Output Accuracy	±0.5% of setting		
mA Output Range	10mA – 300mA / 32kW maximum 10mA – 350mA / 42kW maximum 10mA – 360mA / 50kW maximum	10mA – 420mA / 50kW maximum 10mA – 667mA / 80kW maximum	6mA to 900mA, 110kW maximum
mA Regulation/Accuracy	2% or 2mA or which is larger for 20mA -350mA	2% or 1mA or which is larger for 20mA -420mA	2% or 1mA or which is larger for 20mA -900mA
Filament Output	2 outputs: 15Vac @ 0-6A up to 8A available	1 output: 15Vac @ 0-6A, up to 15A available 2 filament/no grid configuration available	2 outputs: 10Vac @ 0-8A,
Filament Accuracy	±5% of setting	±5% of setting	±2% from 25% to 75%, 5% above
Filament Repeatability	±0.2%		
Starter	HSS configured to match X-Ray tube used		
Interface	Custom serial interface		
Rotation	Up to 120 rpm	Up to 120 rpm	Up to 240 rpm
Configuration	Single Chassis	Two chassis	Four chassis
Grid Option	Dual grid/single filament, 0-4kV @ 0-4kHz (separate assembly)	Dual grid/single filament, 0-4kV @ 0-4kHz (built-in)	n/a
Magnetic Z Deflection Option	n/a	Ground based single channel beam steering	n/a

Please consult factory regarding product configuration availability and regulatory requirements for specific markets